



OMISOLUTIONS

Datasheet

OMI Launch Flex

Flexible and lightweight Launch Fiber

OMI Launch Flex

Features



- Protected Storage — cable stored in a padded bag when not in use
- Easy Mounting — built-in magnets and hook for secure attachment to cabinets and metal surfaces.
- Configurable — compatible with common fiber types and standard optical connectors
- Robust connection — steel-armored cable with integrated traction relief

Description

The OMI Solutions Launch Flex is a flexible, lightweight magnetic launch and receive fiber engineered for accurate and reliable OTDR measurements.

A launch fiber is essential for OTDR testing to expose faults and events close to the fiber ends that can be hidden inside the OTDR dead zone of the first connector.

For complete end-to-end characterization, add a second Launch Flex at the far end of the link to ensure accurate measurement of the final connector.

Configurations

- Singlemode: 500 meters.
- Multimode: 150 meters.

OMISOLUTIONS

Version 1.0

BBT fiberoptic ApS
Skovlytoften 33
DK-2840 Holte

Tel +45 4541 2040
info@bbtfiberoptic.dk
www.bbtfiberoptic.dk

OMI Launch Flex

Specifications

Insertion Loss	SM<0,25dB MM <0,3dB
Return Loss UPC	>50dB
Return Loss APC	>65dB
Dimension	(HxWxD) 24x18x3cm
Weight	0,3kg
Temperature	-40°C - +85°C
Material	Nylon

OMI Launch Flex

Order Information

124-LF-____F-____-____/____

Fiber Type _____

A - Singlemode Fiber (G.652)
B - Singlemode Fiber (G.657)
C - OM2 – 50/125µm fiber
D - OM1 – 62,5/125µm fiber
G - OM3 – 50/125um.
H - OM4 – 50/125um.
I - OM5 – 50/125um.
I - SingleMode fiber (G.654E)

Fiber Length _____

SingleMode (Standard Length 0500m)
MultiMode (Standard Length 0150m)

Connector Type _____

SC - SC/UPC	AL - LC/APC
AS - SC/APC	E2 - E2000/UPC
ST - ST/UPC	EA - E2000/APC
FC - FC/UPC	NC - No Connector
AP - FC/APC	
LC - LC/UPC	

*Please specify both ends